

# UL/CSA OUTPUT RATING SHEET

## OUTPUT I/O (4.8.12.16. and 28 point)

Relay output. type with suffix R.R1 and R2

RATING	
30V dc (Resistive) 120V ac (Tungsten) 250V ac (General Purpose)	2A maximum/point 4A maximum/common (2 or 4 point) 6A maximum/common (8 point) 8A maximum total output (for C4K) 12A maximum total output (for C20P/C20K) 16A maximum total output (for C28P/C28K) 18A maximum total output (for C16P) 20A maximum total output (for C40P/C40K)
30V dc (Resistive)	28A maximum total output (for C60P/C60K)
120V ac (Tungsten)	28A maximum total output (for C60P/C60K)
250V ac (General Purpose)	28A maximum total output (for C60P/C60K)
250V ac (Pilot Duty)	220VA maximum/point 440VA maximum/common (2 or 4 point) 660VA maximum/common (8 point) 880VA maximum total output (for C4K) 1320VA maximum total output (for C20P/C20K) 1440VA maximum total output (for C28P/C28K) 1440VA maximum total output (for C16P) 1440VA maximum total output (for C40P/C40K) 1440VA maximum total output (for C60P/C60K)
120V ac (Pilot Duty)	110VA maximum/point 220VA maximum/common (2 or 4 point) 330VA maximum/common (8 point) 440VA maximum total output (for C4K) 660VA maximum total output (for C20P/C20K) 880VA maximum total output (for C28P/C28K) 990VA maximum total output (for C16P) 1100VA maximum total output (for C40P/C40K) 1440VA maximum total output (for C60P/C60K)

Triac output. type with suffix S

RATING	
250V ac (Resistive) 250V ac (Tungsten)	0.2A maximum/point

## Triac output. type with suffix S1 and S2

RATING	
250V ac (Resistive) 250V ac (Tungsten)	1A maximum/point 2A maximum common (for C4K) 4A maximum common (4 point) 6A maximum common (8 point) 4A maximum total output (for C4K) 8A maximum total output (for C20P/C20K) 12A maximum total output (for C28P/C28K) 14A maximum total output (for C16P) 16A maximum total output (for C40P/C40K) 20A maximum total output (for C60P/C60K)
250V ac (Pilot Duty)	100VA maximum/Point 200VA maximum/common (for C4K) 200VA maximum/common (4 Point of C16P) 200VA maximum common (4 Point) 400VA maximum common (8 Point) 400VA maximum total output (for C4K) 800VA maximum total output (for C20P/C20K) 1200VA maximum total output (for C28P/C28K) 900VA maximum total output (for C16P) 1440VA maximum total output (for C40P/C40K) 1440VA maximum total output (for C60P/C60K)

## Transistor output. type with suffix T

RATING	
24V dc (Resistive) 24V dc (Tungsten)	0.5A maximum/point

## Transistor output. type with suffix T1 and T2

RATING	
24V dc (Resistive) 24V dc (Tungsten)	1A maximum/point 2A maximum/common (for C4K) 4A maximum/common (4 point) 6A maximum common (8 point) 4A maximum total output (for C4K) 8A maximum total output (for C20P/C20K) 12A maximum total output (for C28P/C28K) 14A maximum total output (for C16P) 16A maximum total output (for C40P/C40K) 15A maximum total output (for C60P/C60K)